

BC9306S LED Explosion Proof Light (Bracket)

TORMIN



Ex marking: Ex db eb IIC T6/T5/T4 Gb
Ex tb IIIC T80°C/T95°C/T130°C Db,IP66

Application

- Ideal to be used in the oilfield, chemical industry, offshore drilling platform, steel industry, petroleum etc.
- Gas explosive environment: Group IIA, IIB, IIC.
- Zone 1, zone 2; zone 21, zone 22.





Characteristics

- It is made using a special aluminum housing, all exposed fasteners and bracket adopt 304 stainless steel. Using high-tech anti-corrosion surface treatment technology, suitable for long-term highly corrosive environment of offshore oil platforms, oil drilling platform, chlor-alkali, vulcanization cyanide, etc.
- A full range of high conductivity material accelerate convection cooling structure, effective guarantee long-term use in high temperature environments.
- Variety of light distribution, variety of installation types, an effective solution to beautify workshop and device platform.
- The shell is made of high-tech surface coating technology, corrosion resistant, waterproof and dust proof, suitable for harsh environments.
- Optoelectronic integrated technology, no dark spot, no ghosting, the average light efficiency of whole lamp can reach to 120 lm/W, energy-saving is 60% more than Metal Halide Lamp.
- Taiwan Meanwell power supply or same quality power supply, power factor above 0.98, high reliability and long time service life.
- Independent wiring chamber, safe and easy installation and maintenance.
- Quick replay light source without welding.
- Intelligent control functions can be realized.(Dimming: 1-10VDC, PWM, Carrier, DALI, etc.)

Main Specification

Item	Technical Parameters
Input voltage (V)	90~264VAC
	18~43VAC/ 18~55VDC
Rated frequency	50Hz / 60Hz
Light source	LED
CRI (Ra)	70 (80 optional)
Life time (h)	50,000
CCT	5000K(3000K/4000K optional)
Cable entry	M20×1.5, NPT1/2"
Terminals	Multi core: $\leq 2.5\text{mm}^2$
	Single core: $\leq 4\text{mm}^2$
Dimension (mm)	245×260×270
Net weight (kg)	4.9

Ordering reference

Ordering reference	Picture	Rated Wattage (W)	Light output (lm)	Space height ratio	Mounting height (m)	Light distribution curve(1000cd/lm)	Equivalent to	
							MH	
BC9306S-L30-60°×80°		30W	3500	1.25	3~6m		70W	
BC9306S-L40-60°×80°		40W	4600				100W	
BC9306S-L50-60°×80°		50W	5600		5~8m		100~150W	
BC9306S-L60-60°×80°		60W	6900				150W	
BC9306S-L80-60°×80°		80W	8800				175W	
BC9306S-L30-90°×110°		30W	3400	1.75	3~6m		70W	
BC9306S-L40-90°×110°		40W	4400				100W	
BC9306S-L50-90°×110°		50W	5600		5~8m		100~150W	
BC9306S-L60-90°×110°		60W	6700				150W	
BC9306S-L80-90°×110°		80W	8400				175W	
BC9306S-L30-200°		30W	2800	1.75	3~6m	70W		
BC9306S-L40-200°		40W	3700			100W		
BC9306S-L50-200°		50W	4500		4~8m		100~150W	
BC9306S-L60-200°		60W	5400				150W	
BC9306S-L80-200°		80W	6800				175W	
Input voltage: 18~43VAC/ 18~55VDC								
BC9306S-L25L-60°×80°		25W	2900	1.25	3~6m		70W	
BC9306S-L40L-60°×80°		40W	4600				100W	
BC9306S-L60L-60°×80°		60W	6900		5~8m		150W	
BC9306S-L25L-90°×110°		25W	2700	1.75	3~6m		70W	
BC9306S-L40L-90°×110°		40W	4400				100W	
BC9306S-L60L-90°×110°		60W	6700		5~8m		150W	
BC9306S-L25L-200°		25W	2400	1.75	3~6m		70W	
BC9306S-L40L-200°		40W	3700				100W	
BC9306S-L60L-200°		60W	5400		4~8m		150W	


Note 1: Lens can be customized 40°, 60°, 80°, 100°

BC9306S LED Explosion Proof Light (Bracket)


TORMIN

Drawing of dimension (Dimensions in mm)



Seat mounting





Ceiling mounting



Side wall mounting



Pole mounting



Accessories ordering information(optional)

Ordering reference	Item no	Specification	quantity	note
P07	1	Water proof plug M20	1	φ 8~ φ 12mm cable
	2	Vertical Mounting pole	1	φ 40~ φ 50mm pole