

Ex

LED

IP
66

CE



Ex marking: Ex db eb mb IIC T6 Gb



Application

This product is suitable for accident repair, engineering construction and various flammable and explosive places as portable lighting.

Characteristics

- Freely switch between spotlight and floodlight modes, when the lamp is working, press and hold the switch for 5 seconds to switch;
- Foldable handle, suitable for towing comfortably during moving;
- The projection angle of the lamp head can be adjusted freely within the range of 360 degrees horizontally and 135 degrees of pitch. You can also remove the lamp head and hold the lamp head at any angle for illumination
- The lamp head can be adjusted freely within the height range of 1.7 meters by inserting the lifting rod, or can be freely adjusted within the height range of three meters with a tripod;
- The light source adopts the famous brand, and the battery uses the famous brand long-life battery, which can effectively guarantee the life of the product;
- Protection grade reaches IP66, can effectively resist heavy rain;
- Press and hold for 3 seconds to automatically detect the power, flash 5 times for full power, flash 4 times for 80% power, and so on.

Main Specification

Specification		Unit	Spotlight	Floodlight
Rated Voltage		V	24	
Rated capacity		Ah	15	
Rated wattage	High	W	30	30
	Low		15	15
Beam angle		degree	3	95
Lighting output	High	lm	3088	2485
	Low		1373	1244
Continuous lighting time	High	h	13	13
	Low		28	28
Average life time		h	100,000	
Time of Charging		h	≥8	
Service life of battery		Recycle	≈1000	
Dimension		mm	255×250×610	
Net weight		Kg	15.0	