

ZW3500D All-dimensional Remote Control Light Tower (LED)

TORMIN

LED

**IP
65**



Controller



25°

60°x80°

Application

This product is suitable for a variety of large-scale construction work, maintenance repair, incident handling and disaster relief work site, high brightness lighting needs




Characteristics

- 2* 240W of LED lamp light efficiency up to 120lm/W, can replace two 400W metal halide lamp, energy consumption reduced by 60%.
- Imported LED light source, seismic performance under vibration environment, life is 10 times more than traditional metal halide lamp.
- Wireless remote control + manual control: can remote control lifting poles and lamps with 30m, the switch on the generator also can be used to achieve the same functionality
- Full-cycle thermal design, suitable for hot and humid environment; the up and down ventilation fin structure, can avoid dust.
- Using the same grade or brand Meanwell AC and DC wide voltage constant power supply, power factor up to 0.98.
- Lighting angle locking device is provided to ensure vibration environments irradiation direction is not displaced.
- The bottom of the generator set is equipped with casters, can turn 360°.

Main Specification

Item		Technical Parameters	
Type		ZW3500D-18°/25°	ZW3500D-60°x80°
Generator fullfill continuous working time		13h	
Lifter	Minimum height	1.75m	
	The maximum rise height	4.5m	
Generators	Rated output power / fuel rated capacity	2000W / 15L	
Size	length × width × height	1500 × 500 × 800mm	
Weight	Lamp+lamp panel	15Kg	14Kg
	Lifter	9Kg	
	Generator set	45Kg	

Ordering Reference

Model number	Rated voltage (V)	Rated Wattage (W)	Light output (lm)	Light average life (h)	Light distribution curve (1000cd/lm)	Equivalent to Metal Halide
ZW3500D-L150×2-60°×80°	220VAC	150×2	17300×2	50000		400W×2
ZW3500D-L240×2-60°×80°		240×2	26700×2			400W×4
ZW3500D-L150×2-18°		150×2	14600×2	50000		400W×2
ZW3500D-L240×2-25°		240×2	20300×2	50000		400W×4

