

ZW3520C Portable Mobile Light Tower (LED)

TORMIN

LED

**IP
65**



Characteristics

- 2*100W LED lamp luminous efficiency up to 120 lm / W, can replace 2*250W metal halide lamp, reduce energy consumption by 60%.
- Imported LED light source, seismic performance under vibration environment, life is 10 times more than traditional metal halide lamp
- 3 section adjustable telescopic gas bar, can be any lift in the 1.45m-2.8m range
- Lamps can be quickly assembled and disassembled by hand, full-cycle thermal design, long-term operating environment for high temperature and high humidity; up and down Ventilation fin structure avoid dust
- Lighting angle locking device is provided to ensure vibration environments irradiation direction is not displaced.

Application

This product is suitable for use as large area illumination solution at the working sites of constructions, maintenance, repair, accident spot, and disaster relief etc.



Main Specification

Item		Technical Parameters
Type		ZW3520C
Lamp	Rated voltage	220VAC
	Lamp average life	100,000h
Generator fulfill continuous working time		>6h
Lifter	Minimum height	1.45m
	The maximum rise height	2.8m
Generators	Rated capacity	12V/8.3A
	Rated output power / fuel rated capacity	900W/3.8L
Size	length × width × height	720 × 475 × 1600
Weight		47.5Kg

Ordering Reference

Model number	Rated wattage (W)	Light output (lm)	Light distribution curve (1000cd/lm)	Equivalent to
				Metal Halide
ZW3520C-L60×2-18°	60×2	5600×2		150W×2
ZW3520C-L100×2-18°	100×2	7800×2		250W×2
ZW3520C-L60×2-60°×80°	60×2	6500×2		150W×2
ZW3520C-L100×2-60°×80°	100×2	9000×2		250W×2