

LED

IP
66



Application

This product is suitable for a variety of large-scale construction work, maintenance repair, incident handling and disaster relief work site, high brightness lighting needs

Characteristics

- Imported LED light source, seismic performance under vibration environment, lifetime is 10 times more than traditional metal halide lamps 3 section adjustable telescopic gas bar, can be any lift in the 1.2m-2.8m range
- Lamps can be quickly assembled and disassembled by hand.
- Full-cycle thermal design, suitable for hot and humid environment; the up and down ventilation fin structure, can avoid dust
- Lighting angle locking device is provided to ensure vibration environments irradiation direction is not displaced

Main Specification

Item		Technical Parameters
Type		ZW3530
Lamp	Rated voltage	220VAC
	Rated frequency	50Hz/60Hz
	Lamp average life	100,000h
Lifter	Minimum height	1.2m
	The maximum rise height	2.8m
Size	length × width × height	242 × 200 × 320mm
Weight	Lamp+lamp panel	6.5Kg / 7Kg
	Lifter	2kg

Ordering Reference

Model number	Rated wattage (W)	Light output (lm)	Light distribution curve (1000cd/lm)	Equivalent to
				Metal Halide
ZW3530-L40×2-18°	40×2	3500×2		100W×2
ZW3530-L40×2-60°×80°	40×2	4100×2		100W×2