



LIGHTING FIXTURES AND EQUIPMENT

Lighting for Hazardous and Industrial Areas



ZHEJIANG TORMIN ELECTRICAL CO.,LTD.

■ Address: NO.2, GANGTENG ROAD, YONGXING SUBDISTRICT, LONGWAN DISTRICT, WENZHOU CITY, ZHEJIANG PROVINCE, CHINA, 325024
 ■ Tel: +86 577 56966366 +86 577 56966616 Fax: +86 577 56966166
 ■ E-mail: sales@tormin-lighting.com [Http://www.tormin-lighting.com](http://www.tormin-lighting.com)



Brief Catalogue 04.09.2025

ZHEJIANG TORMIN ELECTRICAL CO.,LTD.

Zhejiang Tormin Electrical Co., Ltd (stock code: 839558), established in 2003, is a high—tech civilian enterprise that specializes in R & D, manufacturing and selling of industrial lamps. Tormin products are widely used in the fields of petroleum, chemical industry, electric power, mining, metallurgy, railway, fire protection, etc. Tormin industrial lights are made to the highest world standard in the industry, gets the European ATEX explosion—proof certification, IECEx international explosion—proof certification; CE, ROHS and other international certification, etc. international quality standard certification. Tormin passes ISO9001 quality control system, ISO14001 environment management system and OHSAS18001 Occupation Health Safety Management System. Tormin is one of the China Illuminating Engineering Society outstanding members, the National Light Industry explosion—proof lighting standard drafting units; has the honor to get the "National High—tech Enterprise", "National Torch Plan", "Wenzhou Famous Brand", "Wenzhou city famous trademark", "Zhejiang Science and Technology SMEs ", " patent model enterprise in Wenzhou City ", " patent protection of key enterprises "and" enterprise technology research and development center in Wenzhou City "; product has passed the national Coal Mine Safety certification, the State quality supervision and Inspection Center and lamps national explosion—proof electrical products for Quality Supervision and Inspection Center and other authoritative national certification bodies. Tormin has a strong R & D and serious and pragmatic team. Adhere to the "dedicated, innovative and stable" business philosophy, through continuous innovation, with more than 20 years of market experience, always user-oriented, and constantly meet the needs of users as the core, through continuous improvement, products in the explosive gas, dust, corrosion, In harsh environments such as vibration, high temperature, and high humidity, they can work safely and reliably for a long time, and they have made many innovations in the use, maintenance, and intelligence of their products, making them more efficient and user-friendly. Tormin products not only meet the basic lighting needs, but also attach more importance to light and environment, and the perfect integration of light and biology, providing safer and more reliable energy-saving and environmentally friendly products for the era of smart lighting. In accordance with the purpose of the industry to serve the country, the determination of being a hundred years of brand enterprises and the aim of winning the win-win situation of customers, employees, and enterprises, Tormin create an excellent platform for the continuous joining elites and build the first-class brand of industrial lighting in China.

We are convinced that our leading role in future will also contribute to your success.



■ Low height region of pedestrian intensive, like offshore oil, chemical device platform, oil tankers of various channels, cabin, etc.

■ EX Mark: Ⓜ II 2G Ex db eb IIC T6 Gb
Ⓜ II 2D Ex tb IIIC T80°C Db

■ Cable Entry: M25×1.5, NPT3/4", G3/4" (Standard);
M20×1.5, NPT1/2" (attached with adaptor)



BC5401




ATEX Cert No.: CNEX 23 ATEX 0008 X
IECEX Cert No.: IECEX CNEX 23.0005X

	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size (mm)	Replaces Fluorescent lamp
BC5401-L2×10	100~240VAC	2×10W	2400	6.6	class I, zone1 &zone2, zone21 &zone22	780×180×110	2×20W
BC5401-L2×20		2×20W	4800	10.7		1390×180×110	2×40W
BC5401-L2×25		2×25W	5100	10.7		1390×180×110	2×50W



BC5402A



ATEX Cert No.: SEV 19 ATEX 0165 X
IECEX Cert No.: IECEX SEV 19.0029

Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size (mm)	Replaces energy saving lamp
BC5402A-L30	120~240VAC	30W	3300	3.2	class I, zone1 &zone2, zone21 &zone22	700×182×68	50~70W
BC5402A-L40		40W	4400	3.4		1150×182×68	100W
BC5402A-L60		60W	6300	4.5			150W
BC5402A-L80	200~240VAC	80W	8400	4.7			175W



BC5402B



ATEX Cert No.: SEV 18 ATEX 0152
IECEX Cert No.: IECEX SEV 18.0031

Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size (mm)	Replaces energy saving lamp
BC5402B-L20	100~240VAC	20W	2200	3.2	zone2, &zone22	700×182×68	40W
BC5402B-L40		40W	4400	3.4		1150×182×68	100W
BC5402B-L60		60W	6300	4.5			150W
BC5402B-L80	200~240VAC	80W	8400	4.7			175W



BC5404



ATEX Cert No.: SEV 18 ATEX 0152
IECEX Cert No.: IECEX SEV 18.0031

Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC5404A-L24	100~240VAC	24W	2640	4.3kg(light)+ 2kg(power box)	zone2	1200×300	48W
BC5404A-L36		36W	3960				72W
BC5404A-L48		48W	5280				96W
BC5404A-L60		60W	6600	120W			
BC5404A-L80		80W	8800	160W			
BC5404B-L24		24W	2640	4.3kg(light)+ 2kg(power box)		600×600	48W
BC5404B-L36		36W	3960				72W
BC5404B-L48		48W	5280				96W
BC5404C-L12		12W	1320	2.3kg(light)+ 2kg(power box)		300×600	24W
BC5404C-L18		18W	1980				36W
BC5404C-L24		24W	2640				48W
BC5404C-L36		36W	3960				72W
BC5404C-L48		48W	5280				96W



BC5405



■ Suitable for explosive gas environment of raw material,like fine chemical industry, electronics microelectronics production,clean room, laboratory, operating room.

■ EX Mark: Ex db mb IIC T6 Gb
■ Cable Entry: G3/4 " ,NPT3/4" ,M25×1.5

Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC5405A-L24	100~240VAC	24W	2640	4.3kg(light)+ 2kg(power box)	class I, zone 1 &zone2	1200×300	48W
BC5405A-L36		36W	3960				72W
BC5405A-L48		48W	5280				96W
BC5405B-L24		24W	2640			600×600	48W
BC5405B-L36		36W	3960				72W
BC5405B-L48		48W	5280				96W
BC5405C-L12	100~240VAC	12W	1320	2.3kg(light)+ 2kg(power box)		300×600	24W
BC5405C-L18		18W	1980				36W
BC5405C-L24		24W	2640				48W



BC9102



ATEX Cert NO.: SEV 21 ATEX 0500 X
IECEX Cert NO.: IECEX SEV 21.0002X

■ Suitable for the environment of flammable gas, steam and dust environment, such as Petrochemical Plant, Chemical Plant, Coal Washery, Pharmaceutical Factory, etc.

■ EX Mark: Ⓜ II 2G Ex db eb mb IIC T4/ T5/ T6 Gb
Ⓜ II 2D Ex tb IIIC T130°C/ T95°C/ T80°C Db
■ Cable Entry: M20×1.5

Type	Rated voltage (V)	Wattage (W)	Light efficacy (lm/W)	Net weight (kg)	Application	Size (mm)/ Module Number
BC9102S	120~277VAC	60W	>110lm/W	5	class I, zone1 &zone2, zone21 &zone22	335(L)×212×93/ 1 module
		100W/120W		8.3		335(L)×336×93/ 2 module
		150W/180W		12.4		338(L)×462×93/ 3 module
		240W		15.8		338(L)×586×93/ 4 module
		300W		19.1		338(L)×710×93/ 5 module
*Other wattage not listed can be chosen depends on clients' requirement.						CCT: 3000K, 4000K, 5000K
*Road lighting mounted type could be chosen with "R" mark for 30W~240W with customized accessories .						

■ Factory, street, warehouse, workshop, etc.

■ EX Mark: Ex db eb mb IIC T6 Gb
Ex tb IIIC T80°C Db



BC5407



Type	Rated voltage (V)	Quantity of light source	Light source wattage(W)	Output wattage(W)	Application	Length(mm)	Replaces Fluorescent lamp
BC5401-1×L9	100~240VAC	1	9	9	class I, zone1 &zone2, zone21 &zone22	746	18W
BC5401-1×L13.5		1	13.5	13.5			25W
BC5401-2×L9		2	9	18			36W
BC5401-2×L13.5		2	13.5	27			54W
BC5401-3×L9		3	9	27			54W
BC5401-3×L13.5		3	13.5	40.5			80W
BC5401-1×L18	100~240VAC	1	18	18	class I, zone1 &zone2, zone21 &zone22	1260	36W
BC5401-1×L27		1	27	27			54W
BC5401-2×L18		2	18	36			72W
BC5401-2×L27		2	27	54			108W
BC5401-3×L18		3	18	54			108W
BC5401-3×L27		3	27	81			150W
*The light can be attached with built-in battery to achieve emergency function, One tube turn on as emergency mode.							

■ Suitable for oil mining, refining, chemical industry, power plants and other dangerous places for working lighting.

■ EX Mark: Ex db eb IIB T6/T5 Gb
Ex tb IIIC T80°C/T95°C Db
■ Cable Entry: G3/4 " ,NPT3/4" ,M25×1.5



BC9105



Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC9105-L150	100~240VAC	150W	24200	5	class I, zone 1 &zone2, zone21 &zone22	346×273×115	250W~400W
BC9105-L300		300W	48400	10.5		350×502×115	600W
BC9105-L600		600W	96800	25		675×548×115	1500W
BC9105i-L100		100W	16000	5		346×273×115	175W~250W
BC9105i for intelligent microwave sensing, can detect human or goods movement, adjust the brightness of the light,only a single module can be selected							

■ Suitable for oil mining, refining, chemical industry, power plants and other dangerous places for working lighting.

■ EX Mark: Ex nR IIC T6/T5 Gc
Ex tb IIIC T80°C/T95°C Db
■ Cable Entry: G3/4 " ,NPT3/4" ,M25×1.5



BC9107



Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC9107-L150	100~240VAC	150W	24200	5	class I, zone 1 &zone2, zone21 &zone22	346×273×111	250W~400W
BC9107-L300		300W	48400	10.5		350×502×111	600W
BC9107-L600		600W	96800	25		675×548×111	1500W
BC9107i-L100		100W	16000	5		346×273×111	175W~250W
BC9107i for intelligent microwave sensing, can detect human or goods movement, adjust the brightness of the light,only a single module can be selected							

■ Grid power, power plants, oil fields, chemical industries, fire protection, railways, and military sectors, etc.

■ EX Mark: Ⓜ II 2G Ex eb ib IIC T4 Gb



BC5409



ATEX Cert No.: TUV 25 ATEX 9321 X
IECEX Cert No.: IECEX TUR 25.0061X

Type	Input voltage range (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size (mm)	Replaces energy saving lamp
BC5409-L3	20~28VDC	3W	290	0.47	class I, zone1 &zone2,	Ø47×244	6W
BC5409-L6		6W	650				12W

■ Suitable for equipment area, stacking and stockyard, like petrochemical plants, chemical plants, pharmaceutical plants, etc.

■ EX Mark: Ⓜ II 2G Ex db eb IIB T6 Gb
Ⓜ II 2D Ex tb IIIC T80°C Db
■ Cable Entry: G3/4"



BC9101



ATEX Cert No.: CNEX 23 ATEX 0009 X
IECEX Cert No.: IECEX CNEX 23.0006X

Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC9101-L25H	100~277VAC	25W	2800	9	class I, zone1 &zone2, zone21 &zone22	326×370×88	70W
BC9101-L40H		40W	4200				100W
BC9101-L60H		60W	5900				150W
BC9101-L80H		80W	7200				175W
BC9101-L25L	20~39VAC/ 20~50VDC	25W	2800	9		326×370×88	70W
BC9101-40L		40W	4200				100W



BC9200



ATEX Cert No.: IMQ 25 ATEX 028X
IECEX Cert No.: IECEX COM 24.0060X

■ Low height region like petrochemical plants, chemical plants, power distribution room, cable channel of power plant, etc.

■ EX Mark: Ⓜ II 2G Ex db eb IIC T6 Gb
Ⓜ II 2D Ex tb IIIC T80°C Db
■ Cable Entry: G1/2", NPT1/2",M20×1.5

Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size (mm)	Replaces energy saving lamp
BC9200-L6	100~240VAC	6W	500	1.3	class I, zone1 &zone2, zone21 &zone22	Ø150×140	18W
BC9200-L12		12W	1000				22W
BC9200-L15		15W	1200				30W
BC9200-L20		20W	1500				45W
BC9200-L6D	20~40VAC/ 20~50VDC	6W	500	1.3	class I, zone1 &zone2, zone21 &zone22	Ø150×140	18W
BC9200-L12D		12W	1000				22W
BC9200-L15D		15W	1200				30W
BC9200-L20D		20W	1500				45W

■ EX Mark: Ex nR II C T6 Gb
Ex tD A21 IP66 T80°C
■ Cable Entry: G3/4 "

BC9311BP



BC9311BS



Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size(mm)	Replaces MH
BC9311BP-L30	100~240VAC	30W	4020	2.2	class I, zone 1 &zone2	φ230×167mm	70W
BC9311BP-L40		40W	5240				100W
BC9311BP-L50		50W	6470				100W
BC9311BP-L60		60W	7390				150W
BC9311BS-L30		30W	4020	3		270×250×167	70W
BC9311BS-L40		40W	5240				100W
BC9311BS-L50		50W	6470				100W
BC9311BS-L60		60W	7390				150W

■ EX Mark: Ex de IIC T6 Gb
Ex tD A21 IP66 T80°C
■ Cable Entry: G1/2"

IP 66

Ta
40

Ta
-40

BC9313P



BC9313S



Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size(mm)	Replaces MH
BC9313P-L25	100~240VAC	25W	4225	1.8	class I, zone 1 &zone2, zone21 &zone22	Φ200×208	50W
BC9313P-L30		30W	5070				70W
BC9313P-L40		40W	6760				100W
BC9313P-L50		50W	8450				100W
BC9313S-L25		25W	4225	2.2		231×157×255	50W
BC9313S-L30		30W	5070				70W
BC9313S-L40		40W	6760				100W
BC9313S-L50		50W	8450				100W

■ EX Mark: Ex d IIC T6 Gb
Ex tD A21 IP66 T80°C
■ Cable Entry: G3/4 "



IP 66

BC9314

[illegible]

■ EX Mark: Ex de IIC T6 Gb
Ex tD A21 IP66 T80°C
■ Cable Entry: G1/2"

IP 66

Ta 40

Ta 40

BC9502

[illegible]

■ EX Mark:  II 2G Ex db IIC T5/ T4/ T3 Gb
 II 2D Ex tb IIIC T95°C/ T130°C/ T195°C Db
■ Cable Entry: M20×1.5, M25×1.5, NPT3/4",
NPT1/2", G3/4"

BC9700



ATEX Cert No.: EPT16 ATEX 2483 X
IECEX Cert No.: IECEX CML 24.01183

Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC9700-L50	100~277VAC	50W	6000	6.3	class I, zone1 &zone2, zone21 &zone22	300×202×332	120W
BC9700-L60		60W	6800				150W
BC9700-L80		80W	8900				175W
BC9700-L100		100W	11600				250W
BC9700-L120		120W	13400				250~400W
BC9700-L150		150W	16100				400W
BC9700-L200		200W	22700				>400W
*Other beam angle available: 40°, 60°, 80°, 100°, 60°×80°, 90°×110°. CCT: 3000K, 4000K, 5000K							

- Flood light in this series can be used for stationary local illumination in coal mines and in other places on explosive hazardous gas(methane-mixtures),coal dust, etc. like coal mine tunnel, cavern, substations, pump room, etc.

■ EX Mark: Ex d I Mb

■ Cable Entry: G3/4"

MA CE Ta40 Ta-20 DGS24/127L(A) DGS35/127L(A) DGS48/127L(A) 	Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Size (mm)	Replaces MH
	DGS24/127L(A)	100~240VAC	24W	2000	4.1	422×177×77	70W
	DGS35/127L(A)		35W	3200			100W
	DGS48/127L(A)		48W	3900			100~150W

- Flood light in this series can be used for stationary local illumination in coal mines and in other places on explosive hazardous gas(methane-mixtures),coal dust, etc. like coal mine tunnel, cavern, substations, pump room, etc.

■ EX Mark: Ex d I Mb

■ Cable Entry: G3/4"

MA Ta40 Ta-20 DGS20/127L(C) DGS30/127L(C) DGS45/127L(C) 	Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Size (mm)	Replaces MH
	DGS20/127L(C)-P	100~240VAC	20W	1950	2.7	Ø230×180	50W
	DGS30/127L(C)-P		30W	2750			70W
	DGS45/127L(C)-P		45W	4100			100W

- Flood light in this series can be used for stationary local illumination in coal mines and in other places on explosive hazardous gas(methane-mixtures),coal dust, etc. like coal mine tunnel, cavern, substations, pump room, etc.

■ EX Mark: Ex d I Mb

■ Cable Entry: G3/4"

MA Ta40 Ta-20 DGS20/127L(C) DGS30/127L(C) DGS45/127L(C) 	Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Size (mm)	Replaces MH
	DGS20/127L(C)-S	100~240VAC	20W	1950	3.2	218×230×268	50W
	DGS30/127L(C)-S		30W	2750			70W
	DGS45/127L(C)-S		45W	4100			100W

- Flood light in this series can be used for stationary local illumination in coal mines and in other places on explosive hazardous gas(methane-mixtures), coal dust, etc. like coal mine tunnel, cavern, substations, pump room, etc.

■ EX Mark: Ex d I Mb

■ Cable Entry: G3/4"

MA

Ta

40

Ta

-20

DGC20/127L(A)

DGC30/127L(A)

DGC45/127L(A)



Type	Rated voltage (V)	Wattage (W)	Light output (lm)	Net weight (kg)	Size (mm)	Replaces MH
DGC20/127L(A)	100~240VAC	20W	1800	5.5	Ø230×218	50W
DGC30/127L(A)		30W	2600			70W
DGC45/127L(A)		45W	3825			100W
*This coal mine light could be attached with bracket, Material is 304 stainless steel						

- suitable for explosive gas environment of raw material,like fine chemical industry, electronics microelectronics production,clean room, laboratory, operating room.


■ EX Mark: Ex nR IIC T6 Gc

■ Cable Entry: G3/4 " ,NPT3/4" ,M25×1.5

ABS

Ex

BC5404J



Type	Rated voltage (V)	Wattage (W)	emergency wattage(W)	emergency light output(lm)	emergency duration(min)	Net weight (kg)	Application	Size (mm)	Replaces MH							
BC5404AJ-L24-L5	100~240VAC	24W	5W	550	≥180	4.3(light)+ 2.9(Emergency box)	zone2	300×600	48W							
BC5404AJ-L36-L5		36W							72W							
BC5404AJ-L48-L5		48W							96W							
BC5404BJ-L24-L5		24W						1200×300	48W							
BC5404BJ-L36-L5		36W							72W							
BC5404BJ-L48-L5		48W							96W							
BC5404CJ-L24-L5		24W				2.3(light)+ 2.9(Emergency box)		600×600	48W							
BC5404CJ-L36-L5		36W							72W							
BC5404CJ-L48-L5		48W														
									96W							

- suitable for explosive gas environment of raw material,like fine chemical industry, electronics microelectronics production,clean room, laboratory, operating room.

■ EX Mark: Ex db mb IIC T6 Gb

■ Cable Entry: G3/4 " ,NPT3/4" ,M25×1.5

ABS

production, clean room, laboratory, operating room.

Ex

BC5405J



Type	Rated voltage (V)	Wattage (W)	emergency wattage(W)	emergency light output(lm)	emergency duration(min)	Net weight (kg)	Application	Size (mm)	Replaces MH			
BC5405AJ-L24-L5	100~240VAC	24W	5W	550	≥180	4.3(light)+ 2.9(Emergency box)	zone2	300×600	48W			
BC5405BJ-L24-L5		24W						48W				
BC5405BJ-L36-L5		36W						72W				
BC5405BJ-L48-L5		48W						96W				
BC5405CJ-L24-L5		24W				2.3(light)+ 2.9(Emergency box)		600×600	48W			
BC5405CJ-L36-L5		36W							72W			
BC5405CJ-L48-L5		48W							96W			

*Option to use only the emergency function

- Low height region of pedestrian intensive, like offshore oil, chemical device platform, oil tankers of various channels, cabin, etc.

■ EX Mark: Ⓜ II 2G Ex db eb IIC T6 Gb
Ⓜ II 2D Ex tb IIIC T80 °C Db

■ Cable Entry: M25×1.5, NPT3/4", G3/4"(Standard);
M20×1.5, NPT1/2",
(attached with adaptor)



IECEx

Ta

55

Ta

-25

IP

66

BC5401

(Emergency)





M20×1.5, NP11/2"

(attached with adaptor)

Type	Rated voltage (V)	Wattage (W)	Emergency wattage (W)	Light output (lm)	Emergency duration (min)	Net weight (kg)	Application	Size (mm)	Replaces Fluorescent lamp
BC5401-L2×10	100~240VAC	2×10W	1×10W	1800(Normal)/900(Emergency)	180min	6.6(Lamp)/2.9(Emergency box)	class 1, zone1 & zone2, zone21 & zone22	780×180×110	2×20W
BC5401-L2×20		2×20W	1×20W	3600(Normal)/1800(Emergency)	90min	10.7(Lamp)/2.9(Emergency box)		1390×180×110	2×40W
*Equipped with explosion proof emergency box BXP01; only one tube lighting when emergency.									

- Low installation height equipment area like petrochemical plants, chemical plants, pharmaceutical factory, polishing plant, etc.

■ EX Mark: Ⓜ II 2G Ex db IIC T6 Gb
Ⓜ II 2D Ex tb IIIC T80 °C Db

■ Cable Entry: M20×1.5, M25×1.5, NPT3/4",
NPT1/2", G3/4"

ABS Ex IECEx IP66 Ta50 Ta-25 BXP01  ATEX Cert No.: EPT16 ATEX 2510 X IECEx Cert No.: IECEx CML 24.0117X	Type	Rated voltage (V)	Wattage (W)	Emergency duration (min)	Output voltage (V)	Net weight (kg)	Application	Size (mm)
	BXP01	100~240VAC	30W	60min	220VDC	2.9	class I, zone1 & zone2, zone21 & zone22	238×222×106
			20W	90min				
			10W	180min				



■ Equipment area, stacking and stockyard, like petrochemical plants, chemical plants, pharmaceutical plants, etc.

■ EX Mark: Ex d IIB T6 Gb
Ex tD A21 IP66 T80℃

■ Cable Entry: G3/4"

BC9101A
BC9101B



Type	Rated voltage (V)	Wattage (W)	Emergency wattage (W)	Emergency light output (lm)	Emergency duration (min)	Net weight (kg)	Size (mm)	Replaces MH
BC9101A-L25-15	100~240VAC	25W	15W	1800	120min	9	370×326×88	70W/ 35W
BC9101A-L40-15		40W	15W	1800				100W/ 35W
BC9101A-L60-15		60W	15W	1800				150W/ 35W
BC9101A-L25-25	100~240VAC	25W	25W	3000	70min	9	370×326×88	70W/ 50W
BC9101A-L40-25		40W	25W	3000				100W/ 50W
BC9101A-L60-25		60W	25W	3000				150W/ 50W
BC9101B-L15	100~240VAC	/	15W	1800	120min	9	370×326×88	/ 35W
BC9101B-L25		/	25W	3000	70min			/ 50W

■ Suitable for oil mining, refining, chemical industry, power plants and other dangerous places for working lighting.

■ EX Mark: Ex de IIB T5/T6 Gb
Ex tb III C T80℃ Db

■ Cable Entry: G3/4", NPT3/4", M25×1.5

Ex

BC9105J



Type	Rated voltage (V)	Wattage (W)	emergency wattage(W)	light output(lm)	emergency duration(min)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC9105J-L80-L5	100~240VAC	80W	5W	12800	≥180	5	class I, zone 1 &zone2, zone21 &zone22	346×273×115	150W-175W
BC9105J-L80-L10		80W	10W	12800	≥90				
BC9105J-L5		/	5W	/	≥180				
BC9105J-L10		/	10W	/	≥90				
*BC9105B with only emergency function									

■ Suitable for oil mining, refining, chemical industry, power plants and other dangerous places for working lighting.

■ EX Mark: Ex nR IIC T6 Gc
Ex tb III C T80℃ Db

■ Cable Entry: G3/4",NPT3/4",M25×1.5

Ex

BC9107J



Type	Rated voltage (V)	Wattage (W)	emergency wattage(W)	light output(lm)	emergency duration(min)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC9107J-L80-L5	100~240VAC	80W	5W	12800	≥180	5	zone2, zone21 &zone22	346×273×111	150W-175W
BC9107J-L80-L10		80W	10W	12800	≥90				
BC9107J-L5		/	5W	/	≥180				
BC9107J-L10		/	10W	/	≥90				
*BC9107B with only emergency function									

■ Suitable for emergency lighting to low installation height region in extreme climate, like offshore oil, chemical equipment platforms, tankers, ships, docks, piers, etc.

■ EX Mark: Ⓜ II 2G Ex db eb IIC T6/T5 Gb
Ⓜ II 2D Ex tb IIIC T80℃/ T95℃ Db
■ Cable Entry: M20×1.5, NPT1/2" (P type/ S type)
M25×1.5, NPT3/4", G3/4" (P type)



BC9306AP/BP



BC9306AS/BS



ATEX Cert No.: EPT16 ATEX 2484 X
IECEX Cert No.: IECEx CML 24.0116X

Type	Rated voltage (V)	Wattage (W)	Emergency wattage (W)	Emergency light output (lm)	Emergency duration (min)	Net weight (kg)	Application	Size (mm)	Replaces MH
BC9306AP-L40-15	100~240VAC	40W	15W	1800	120min	4.2	class I, zone1 &zone2, zone21 &zone22	Ø230×270	100W/ 35W
BC9306AP-L40-25			25W	3300	70min				100W/ 50W
BC9306BP-L15		/	15W	1800	120min				/ 35W
BC9306BP-L25			25W	3300	70min				/ 50W
BC9306AS-L40-15	100~240VAC	40W	15W	1800	120min	4.9	class I, zone1 &zone2, zone21 &zone22	245×260×270	100W/ 35W
BC9306AS-L40-25			25W	3300	70min				100W/ 50W
BC9306BS-L15		/	15W	1800	120min				/ 35W
BC9306BS-L25			25W	3300	70min				/ 50W
*The lamp can be matched with a lens: 40°, 60°, 80°, 100°, 200°, 60°×80°, 90°×110°						CCT: 3000K, 4000K, 5000K.			



BXP02



ATEX Cert No.: CNEX 23 ATEX 0025 X
IECEX Cert No.: IECEx CNEX 23.0023X

■ This product is widely used for low installation height equipment area like petrochemical plants,chemical plants,pharmaceutical factory,polishing plant ,etc.

■ EX Mark: Ⓜ II 2G Ex db IIC T6 Gb
Ⓜ II 2D Ex tb IIIC T80℃ Db
■ Cable Entry: M20×1.5, M25×1.5, NPT3/4", NPT1/2", G3/4"

Type	Rated voltage (V)	Wattage (W)	Emergency wattage(W)	Emergency duration(min)	Rated capacity	Net weight (kg)	Size (mm)
BXP02A-L50-L5	100~240VAC	50W	5W	≥90min	7.4V 2600mAh	2.5	240×230×105.5
BXP02A-L40-L15/25		40W	15W/25W	≥180min/≥90min	14.8V 2600mAh		
BXP02B-L5/10		Max200W	5W/10W		7.4V 2600mAh		
BXP02B-L15/25		/	15W/25W		14.8V 2600mAh		

■ This product is widely used for emergency lighting in hazardous locations.

■ EX Mark: Ex d IIC T6 Gb
Ex tD A21 IP66 T80℃

■ Cable Entry: G3/4 "

Ex

TM-ZFZD-E6W-BC5200



Type	Rated voltage (V)	Wattage (W)	Emergency wattage(W)	Emergency duration(min)	Net weight (kg)	Application	Size (mm)
TM-ZFZD-E6W-BC5200	220VAC	2×3W	2×3W	≥90min	2.9	class I, zone 1 &zone2, zone21 &zone22	255×243×110

■ Suitable for plant platforms, equipment floor areas, main and auxiliary workshops, access roads, pipelines, combined stations, transfer stations, pump and valve sheds, tanks, material sample ports, stacks, silo rooms, warehouses, etc.

■ EX Mark: Ex d IIC T6 Gb
Ex tD A21 IP66 T85℃

■ Cable Entry: G3/4 "

Ex

TM-ZLZD-E40W-BC9302



Type	Rated voltage (V)	Wattage (W)	Emergency wattage(W)	Emergency duration(min)	Net weight (kg)	Application	Size (mm)
TM-ZLZD-E40W-BC9302	220VAC	40W	15W	90min	5	class I, zone 1 &zone2, zone21 &zone22	φ 240×220

■ This product is widely used for emergency lighting in hazardous locations.

■ EX Mark: Ⓜ II 2G Ex db eb II C T6 Gb
Ⓜ II 2D Ex tb III C T80℃ Db
■ Cable Entry: G3/4"



BC4210



BC5210



ATEX Cert NO.: IMQ 22 ATEX 037X
IECEX Cert NO.: IECEx IMQ 22.0008X

Type	Rated voltage (V)	Wattage (W)	Light color	Emergency duration(min)	Emergency mode	Application	Size (mm)
BC4210	100~240V AC	1.5W	Green (Standard)	180min	Always lighting on (power on/ off) (Standard)	3.5	373×165×64
BC5210		2W	White (Standard)		Only emergency lighting (power off) (Standard)		



BHD01 **BHD02**
Explosion Proof Junction Box

Type	BHD01A	BHD01B	BHD02
Rated Vol.	≤500V		
Rated Current	20A		
Terminal Blocks	2	2	4
Inlet Thread	G3/4	M25×1.5 or M20×1.5 or NPT3/4" or NPT1/2"	
Outer Diameter Of Inlet Cable	Depends on the cable connecting accessories		
Weight	1.2kg	0.8kg	
Size	185×185×75mm	116×116×75mm	
Ex Mark	Ex db IIC T6 Gb / Ex tb IIIC T80°C Db IP66		



BHD05-A~K
Explosion Proof Junction Box

Rated Vol.	≤500V
Rated Current	20A
Terminal Blocks	4
Inlet Thread	G Type, M Type, NPT type optional
Outer Diameter Of Inlet Cable	Depends on the cable connecting accessories
Size	Base on the spec
Ex Mark	Ex db IIC T6 Gb Ex tb IIIC T80°C Db



BZA5200 Series Explosion-proof master controller

Type	BZA5200-□□
Rated Vol.	220/380V(A/B type); High/ Low voltage optional(D type)
Rated Current	10A
Inlet Thread	G3/4" or Base on request
Outer Diameter Of Inlet Cable	Depends on the cable connecting accessories
Material	Aluminum alloy
Ex Mark	Ex db IIC T6 Gb Ex tb IIIC T80°C Db



BZM Series Explosion-proof lighting switch

Type	BZM-□□
Rated Vol.	220V/230V/250V
Rated Current	10A/16A/20A
Inlet Thread	G3/4" or M25×1.5 or NPT3/4"
Outer Diameter Of Inlet Cable	Depends on the cable connecting accessories
Size	130x160x101mm
Ex Mark	Ex db IIC T6 Gb Ex tb IIIC T80°C Db



BXJ5310 Series Explosion Proof Junction Box

Type	BXJ5310-□□	BXJ5310-□□
Rated Vol.	≤690V	36VDC
Rated Current	□690A	□5A
Inlet Thread	G3/4" or Base on request	G3/4" or Base on request
Outer Diameter Of Inlet Cable	Depends on the cable connecting accessories	Depends on the cable connecting accessories
Material	Aluminum alloy	Aluminum alloy
Ex Mark	Ex eb IIC T4...T6 Gb Ex tb IIIC T130°C...T80°C Db	Ex ia IIC T6 Ga Ex tb IIIC T80°C Db



BXJ8310 Series Explosion Proof Junction Box

Type	BXJ8310-□□	BXJ8310-□□
Rated Vol.	≤690V	36VDC
Rated Current	□690A	□5A
Inlet Thread	G3/4" or Base on request	G3/4" or Base on request
Outer Diameter Of Inlet Cable	Depends on the cable connecting accessories	Depends on the cable connecting accessories
Material	ABS	ABS
Ex Mark	Ex eb IIC T4...T6 Gb Ex tb IIIC T130°C...T80°C Db	Ex ia IIC T6 Ga Ex tb IIIC T80°C Db



BZC5310 Series Anti-corrosive Explosion Proof Controller

Type	BZC5310-□□
Rated Vol.	220/380VAC, 230/400VAC, 220VDC
Rated Current	10A
Inlet Thread	G1" or Base on request
Outer Diameter Of Inlet Cable	Suitable for φ 13~17mm cable
Material	Aluminum alloy
Ex Mark	Ex eb db mb IIC T6 Gb, Ex tb IIIC T80°C Db Ex db eb IIC T6 Gb, Ex tb IIIC T80°C Db



BZC8310 Series Anti-corrosive Explosion Proof Controller

Type	BZC8310-□□
Rated Vol.	110VAC/DC, 220VAC/DC, 380VAC, 12VAC/DC, 24VAC/DC, 36VAC/DC, 48VAC/DC
Rated Current	10A
Inlet Thread	G1" or Base on request
Outer Diameter Of Inlet Cable	Suitable for φ 12~16mm cable
Material	ABS
Ex Mark	Ex db eb mb IIC T6 Gb, Ex tb IIIC T80°C Db Ex db eb IIC T6 Gb, Ex tb IIIC T80°C Db



Ex E Type Cable Gland

Material	Brass/ Stainless Steel
Gland Type	Cable
Cable type	Unarmored
Ex Mark	Ex e IIC Gb Ex t IIIC Db



Ex D Type Cable Gland

Material	Brass/ Stainless Steel
Gland Type	Cable
Cable type	Unarmored
Ex Mark	Ex d IIC Gb/Ex e IIC Gb Ex tb IIIC Db



BW3210 LED Explosion Proof Work Light(Spot/ Flood mode)

LED Light Source	30W
Rated capacity	15Ah
Run-time	High 13h Work 28h
Ex Mark	Ex db eb IIC T6 Gb
Weight	10.5kg
Size	255×250×610mm



BW4100B Explosion Proof Tracker Light

Warning color	red, yellow, green, blue, white
Flash Fre.	2.7Hz
Runtime	500h
Ex Mark	Ex ia IIC T4 Ga
Weight	100g
Size	70×47×39mm



BW6610A Multifunction LED Explosion Proof Work Light

LED Light Source	3×3W
Rated capacity	2.6Ah
Run-time	High 8h Work 15h
Ex Mark	Ex db eb mb IIC T6 Gb
Weight	1500g
Size	151×131×272mm



BW6610B Multifunction LED Explosion Proof Work Light

LED Light Source	13W
Rated capacity	2.6Ah
Run-time	High 8h Work 16h
Ex Mark	Ex db eb mb IIC T6 Gb
Weight	1800g
Size	272×127×123mm



BW6210 LED Explosion Proof Searchlight

LED Light Source	1W
Rated capacity	5.2Ah(19.2wh)
Run-time	High 8h Work 40h Flood 55h
Ex Mark	Ex ib IIC T4 Gb
Weight	350g
Size	195×74×115mm



BW6310 LED Explosion Proof Mini Headlight

Item No.	BW6310A	BW6310B
Rated capacity	1.4Ah(5.2wh)	
Run-time	High 4h Work 8h	High 8h Work 16h
Ex Mark	Ex ib IIC T4 Gb	
Weight	85g	
Size	50×65×60mm	



BW7100B High-range Explosion Proof Flashlight

LED Light Source	10W
Rated capacity	6.6Ah(24.4wh)
Run-time	High 3~4h Work 10h
Ex Mark	Ex d IIC T6 Gb
Weight	700g
Size	φ 74×190mm



BW7101A LED Portable Explosion Proof Searchlight

Mode	Mode 1	Mode 2
LED Light Source	3×3W	
Rated capacity	2.6Ah(38.5wh)	
Run-time	High 5h Work 10h	High 7.5h Work 16h
Ex Mark	Ex db ib IIC T6 Gb	
Weight	750g	
Size	φ 67×148mm	



BW7101B LED Portable Explosion Proof Searchlight

Mode	Mode 1	Mode 2
LED Light Source	3×3W	
Rated capacity	2.6Ah(57.7wh)	
Run-time	High 7.5h Work 15h	High 11h Work 16h
Ex Mark	Ex db ib IIC T6 Gb	
Weight	750g	
Size	φ 67×148mm	



BW7300A/B LED Explosion Proof Flashlight

Item No.	BW7300A	BW7300B
LED Light Source	3W	1W
Rated capacity	2.6Ah(9.6wh)	
Run-time	High 4h Work 10h	High 8h Work 18h
Ex Mark	Ex d IIC T6 Gb	
Weight	125g	
Size	φ 28×130mm	



BW7320 LED Explosion Proof Flashlight

Mode	Mode 1	Mode 2
LED Light Source	3W	3W
Rated capacity	2.6Ah(9.6wh)	
Run-time	High 3h Work 9h	High 8h Work 18h
Ex Mark	Ex ib IIC T4 Gb	
Weight	165g	
Size	φ35×152mm	



BW7500A LED Explosion Proof Flashlight

Mode	Mode 1	Mode 2
LED Light Source	5W	
Rated capacity	2.6Ah(19.2wh)	
Run-time	High 4h Work 10h	High 6h Work 10h
Ex Mark	Ex d IIC T6 Gb	
Weight	300g	
Size	φ40×210mm	



BW7500B LED Explosion Proof Flashlight

Mode	Mode 1	Mode 2
LED Light Source	3W	
Rated capacity	2.6Ah(19.2wh)	
Run-time	High 6h Work 10h	High 12h Work 20h
Ex Mark	Ex d IIC T6 Gb	
Weight	300g	
Size	φ40×210mm	



BW6640 LED Explosion Proof Flashlight

Mode	Flashlight	Floodlight
LED Light Source	3W	6W
Rated capacity	3.7V 5.2Ah	
Run-time	High 8h Work 16h	High 4h Work 8h
Ex Mark	Ex ib IIC T4 Gb	
Weight	364g	
Size	φ47×243mm	



BW6650A/B LED Explosion-proof Hand Lamps

Item No.	BW6650A	BW6650B
LED Light Source	15W	
Rated capacity	8Ah	External power supply AC 15-40V DC 12-48V
Run-time	High 7h Work 12h	High 12h Work 12h
Ex Mark	Ex db eb ib mb IIC T6/ T5 Gb	
Weight	1300g	1000g
Size	φ118×311mm	



Wattage	9W	18W
Rated Vol.	220VAC	
IP Code	IP66	
Weight	1.0kg	1.6kg
Size	655×75×86mm	1265×75×86mm



Wattage	2×9W	2×18W
Rated Vol.	220VAC	
IP Code	IP66	
Weight	1.5kg	2.3kg
Size	655×113×86mm	1265×113×86mm



Wattage	30W 40W	60W 80W
Rated Vol.	100~240VAC(200~240VAC for 80W)	
IP Code	IP66	
Weight	3.2kg/3.4kg	4.5kg/4.7kg
Size	700×182×68mm	1150×182×68mm



Wattage	12W 18W 24W 36W 40W	24W 36W 48W 60W 80W
Rated Vol.	220VAC	
IP Code	IP66	
Weight	2.3kg	4.3kg
Size	300×600×15mm	300×1200×15mm



Wattage	24W 36W
Rated Vol.	220VAC
IP Code	IP66
Weight	4.3kg
Size	600×600×15mm



Wattage	80W 100W 120W 150W 180W 240W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	5.2kg (2 Modules); add 1pcs Module add 1kg
Size	L322×363×150mm(2 Modules) Add 1 Module, Length add 78mm



Wattage	50W 100W 150W 200W 250W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	3.3kg(1 Module); add 1pcs Module add 0.7kg
Size	315×L193×130mm(1 Module) Add 1 Module, Length add 45mm



Wattage	300W	400W
Rated Vol.	100~277VAC	
IP Code	IP66	
Weight	8.1kg	9.7kg
Size	599×283×130mm	599×360×130mm



Wattage	50W 100W 150W 200W
Rated Vol.	100~240VAC
IP Code	IP66
Weight	3.5kg(100W)/Watt add 50W,weight add 1.3kg
Size	L403×W295×60mm(100W) Watt add 50W, L add 29mm, W add 32.5mm



Wattage	300W~1200W
Rated Vol.	100~240VAC
IP Code	IP66
Weight	4kgs~7kgs
Size	Base on the wattage



Wattage	100W~300W
Rated Vol.	100~240VAC
IP Code	IP65
Weight	3.5kgs~11.5kgs
Size	Base on the wattage



Wattage	50W 80W 100W 120W 150W	200W
Rated Vol.	100~277VAC/DC	
IP Code	IP66	
Weight	2.5kg	3kg
Size	φ 370×175mm	φ 450×200mm



Wattage	30W 40W 50W 60W	80W
Rated Vol.	100~240VAC	
IP Code	IP66	
Weight	2.2kg	2.7kg
Size	φ 230×167mm	φ 240×195mm



Wattage	30W 40W 50W 60W	80W
Rated Vol.	100~240VAC	
IP Code	IP66	
Weight	3kg	3.5kg
Size	270×250×167mm	275×270×195mm



Wattage	50W 100W 150W 200W 250W
Rated Vol.	100~240VAC
IP Code	IP66
Weight	2.9kg(50W) Watt add 50W,weight add 0.8kg
Size	φ353×270mm(50W) Watt add 50W, H add 40mm



Wattage	300W	400W
Rated Vol.	100~240VAC	
IP Code	IP66	
Weight	7.2kg	8.1kg
Size	φ 353×500mm	φ 353×560mm



Wattage	30W 40W 50W 60W 80W 100W 120W 150W	200W 240W 300W	400W 600W
Rated Vol.	100~277VAC		
IP Code	IP66		
Weight	5kg	10.3kg	20kg
Size	330×273×111mm	350×502×111mm	675×548×111mm



Wattage	18W	36W	48W
Rated Vol.	220VAC		
IP Code	IP66		
Weight	0.72kg	1.2kg	1.5kg
Size	656×75×72mm	1256×75×72mm	1556×75×72mm



Wattage	20W 30W 40W 50W	20W 30W 40W
Rated Vol.	220~240VAC	
IP Code	IP67	
Weight	1.5kg	
Size	703×56×77mm	



Wattage	80W 100W 120W	150W 200W	250W
Rated Vol.	100~277VAC		
IP Code	IP65		
Weight	4.1kg	4.5kg	5.1kg
Size	φ 300×182mm	φ 340×182mm	φ 380×182mm



Wattage	80W 100W 120W	150W 200W	250W
Rated Vol.	100~277VAC		
IP Code	IP65		
Weight	5.3kg	5.7kg	6.3kg
Size	332×340×130mm	352×360×130mm	392×400×130mm



Wattage	80W~300W
Rated Vol.	100~240VAC
IP Code	IP65
Weight	1.2kg~5.3kgs
Size	Base on the wattage



Wattage	100W~300W
Rated Vol.	100~240VAC
IP Code	IP65
Weight	2.5kgs~ 5.5kgs
Size	Base on the wattage



Wattage	5W 7W	9W 12W
Rated Vol.	220VAC	
IP Code	IP42	
Spec	2.5"/3"/3.5"/4"	
Weight	0.2kg	0.3kg
Size	φ 100×47mm	φ 143×57mm




Wattage	18W	36W	48W
Rated Vol.	100~240VAC		
IP Code	IP20		
Weight	1.5kg	3.2kg	6.3kg
Size	600×300×11mm	1200×300×11mm	1200×600×11mm



Wattage	18W	36W
Rated Vol.	100~240VAC	
IP Code	IP20	
Weight	0.95kg	3.1kg
Size	300×300×11mm	600×600×11mm



Wattage	5W	7W
Rated Vol.	220VAC	
Weight	0.1kg	0.15kg
Size	50×96mm	60×119mm



Wattage	8W	16W
Rated Vol.	220VAC	
Weight	0.1kg	0.2kg
Size	600× φ 30mm	1200× φ 30mm




Wattage	16W	2×16W
Rated Vol.	220VAC	
Weight	0.45kg	0.85kg
Size	600× φ 30mm	1200× φ 30mm



Wattage	30W 40W 50W 60W
Rated Vol.	220VAC/DC
Weight	0.85kg
Size	φ 177×194mm



Wattage	12W 14W 24W
Rated Vol.	220VAC
IP Code	IP65
Weight	0.7kg
Size	φ 260×126mm




Wattage	20W 30W	40W 50W 60W
Rated Vol.	220VAC	
IP Code	IP66	
Weight	2kg	3kg
Size	590×182×68mm	1040×182×68mm



Wattage	25W 40W 60W 80W
Rated Vol.	100~240V/24V/36VAC/DC
IP Code	IP66
Weight	4.7kg
Size	300×300×75mm



Wattage	10W 20W
Rated Vol.	220V/12V/24V/36VAC/DC
Switch Mode	Regular /Delay switch
IP Code	IP66
Weight	1.3kg
Size	φ 105×144mm



Wattage	10W 20W
Rated Vol.	220V/12V/24V/36VAC/DC
Switch Mode	Regular /Delay switch
IP Code	IP66
Weight	1.3kg
Size	105×138×144mm



Wattage	50W	100W
Rated Vol.	100~240V AC	
IP Code	IP65	
Weight	1.5kg	1.85kg
Size	φ203*222mm/φ232*226mm	



Wattage	50W	100W
Rated Vol.	100~277V AC	
IP Code	IP65	
Weight	2.4kg	3.2kg
Size	φ183×175mm	φ183×258mm




Wattage	80W 100W 120W
Rated Vol.	100~240VAC/DC
IP Code	IP66
Weight	7.9kg
Size	415×415×91mm




Wattage	30W 40W 50W 60W 80W
Rated Vol.	100~277V/24V/36VAC/DC
IP Code	IP66
Weight	4.9kg
Size	245×260×270mm



Wattage	100W 120W 150W 200W 240W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	7.5kg
Size	295×330×350mm



Wattage	240W 300W 400W 480W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	13kg
Size	602×340×250mm



Wattage	240W 300W 400W 480W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	15kg
Size	602×300×440mm



Wattage	240W 300W 400W 480W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	13kg
Size	602×415×255mm



Wattage	500W~1500W
Rated Vol.	100~277VAC
IP Code	IP66
LED light Source	500W per LED modules
Weight	13.8kgs~31.3kgs
Size	Base on the wattage



Wattage	30W 40W 50W 60W 80W
Rated Vol.	100~240V/24V/36VAC/DC
IP Code	IP66
Weight	3.7kg
Size	180×230×270mm



Wattage	6W 12W 20W
Rated Vol.	100~240V/24V/36VAC/DC
IP Code	IP66
Weight	1kg
Size	180×130×66mm



Wattage	100W 120W 150W 200W
Rated Vol.	100~277VAC
IP Code	IP66
Weight	6.3kg
Size	φ 300×202×332mm



Wattage	60W 80W 100W 120W 150W 180W 240W
Rated Vol.	100~277VAC
IP Code	IP65
Weight	6.5kg(2 Modules); Add 1 module, add 1kg
Size	520(L)×315×100mm(2 Modules) Add 1 module, L add 95mm

